



Minolta di 3510

Specificatii generale tip console tehnologie digital, laser volum lunar maxim recomandat 60 000 viteza max. alb/negru 25 cpm A4 17 cpm A3 format max. document A3 format copie (min. - max.) A6 - A3 prima pagina, negru < 5,3 sec. timp incalzire < 17 sec. tip documentsheets, books and 3-D objects tip suport recomandat plain paper, thick paper, OHP sheet greutate recomandata suport 56-210g/m² rezerva de hartie (standard) 1150 pag.:

- multibypass 150 pag. rezerva maxima hartie 2.500 pag. A4/A3;

total: 3650 pag. capacitate maxima de iesire 1200 pag. procesor 233 MHz memorie (standard) 64 MB memorie maxim (optional) max. 128 MB alimentator documente (ADF): AFR-19 Automat Reversibil 80 pag. A4/A3 fata/verso automatic

Funcție copiator standard functii speciale-

- Text Mode;
- Photo Mode;
- Text/Photo Mode;
- watermark;
- image rotation;
- interrupt Mode;
- booklet creation;
- repetare imagine;
- Criss/Cross Sorting;
- Auto Tray Switching;
- Auto/Manual/Photo Exposure;
- Stapling (single or multi-position) rezolutie maxima 600 X 600 dpi nivele de gri 256 zoom 25 - 400% in 1% increments selectie nr. copii 1-99 memorie lucrari coduri acces sortator de lucrari:
- Cod FN-117 Built in Finisher;
- Cod SK-1 Saddle Kit;
- Cod PK-6 Punch Kit;
- Cod MS-5D Staples;

Controller Pi3505e: PCL5e/PCL6;

Printer Controller Pi3505e/PS: PCL5e/PCL6, PostScript 3 font-uri Printer Controller Pi3505e: PCL Fonts (46 fonts);

Printer Controller Pi3505e/PS:

- PCL Fonts (46 fonts)
- PostScript Font (136 fonts) interfata standard- USB 1.1;
- paralel (IEEE 1284);
- Ethernet 10/100Base-T;
- TokenRing (IEEE 802.5);;
- Network Interface Card (NC-4) Sensor viteza scannare 70 ppm (AFR-19 Reversing Auto Document Feeder) viteza scanare (ADF) 30 ppm rezolutie optica 200 x 200 dpi

rezolutie hardware 600 x 600 dpi nivele de gri 256 compatibilitate TWAIN yes interfata-USB 1.1;

- paralel (IEEE 1284);
- Ethernet 10/100Base-T;
- TokenRing (IEEE 802.5);
- scan-to-URL;
- scan-to-HDD;

Alte specificatii

compatibilitate cu sisteme de operare Printer Controller Pi3505e:

- Microsoft® Windows®98, NT4.0, Me, 2000, XP;

Printer Controller Pi3505e/PS:

- Microsoft® Windows®98, NT4.0, Me, 2000, XP;
- Mac®OS 8.6 or Later;
- Unix (e.g. Solaris, HP-UX, IBM-AIX);
- Linux (e.g. Red Hat, Caldera, SuSE) drivere- PostScript 3 driver for Mac®OS 9.2, 10.2 + PPD File, PDF-Direct Print/Font Download Utility for WIN/MAC;
- PCL6 driver for Microsoft® Windows®98, NT4.0, Me, 2000, XP;
- PCL5e mini driver for Microsoft® Windows®98, NT4.0, Me, 2000, XP descriere software inclus/pre-instalat PageScope Light protocoale de retea suportate Printer Controller Pi3505e: TCP/IP, IPX/SPX;

Printer Controller Pi3505e/PS: TCP/IP, IPX/SPX, AppleTalk;

Scanning: TCP/IP, SMTP, FTP management documente PageScope Cabinet;

PageScope Net Care;

PageScope EMS Plug-Ins;

PageScope Network Setup;

PageScope NDPS Gateway retea de alimentare 220-240 Va.c. ± 10%, 50/60 Hz ± 3%
consum 1340 W dimensiuni (w x d x h) 590 X 650 X 710 mm greutate 74 kg

Pret copiator **450 euro**

Optional scanare, print **70 euro**

Scanner in limita stocului disponibil

Costuri reduse consumabile

1 Flacon toner **18 euro 12 000 pg**

Transport gratuit in Bucuresti

Preturile nu includ T.V.A

Garantie 1 an sau 20000 pg

Posibilitate extindere garantie pana la 3 ani